



- PC 1 PLUG TERMINAL POSITION
- 1 TERMINAL BLOCK POSITION
- RELAY COIL
- SOLENOID
- NORMALLY OPEN, RELAY OR SWITCH CONTACTS
- NORMALLY CLOSED RELAY OR SWITCH CONTACTS
- DIODE #1
- 12V BATTERY
- RESETTABLE CIRCUIT BREAKER

PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS  
 DRAWING IS THE SOLE PROPERTY OF  
 AMERICAN ACCESS INDUSTRIES AND SERVICES  
 ANY REPRODUCTION OR TRANSMISSION  
 OF THIS DRAWING WITHOUT THE WRITTEN  
 PERMISSION OF AAIS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		DATE	2019
DIMENSIONS ARE IN INCHES		DESIGNED BY	S. FROST
FRACTIONAL 1/16"		CHECKED BY	
ANGULAR WHEN 1" = 1"		ENG. APPROV.	
TWO PLACE DECIMAL 1.00"		WFG APPROV.	
THREE PLACE DECIMAL 1.000"		QA	
INTERPRET GEOMETRIC TOLERANCING PER ASME Y14.5		PROJECT	
MATERIAL			
FINISH			
SCALE: 21	WEIGHT:	SHEET 1 OF 1	
SIZE DWG. NO.	REV		
D H58266	0		